

Material data sheet

Insulating strips of
Low Lambda PA 66 GF25,
dry impact resistant

Material data sheet

**Insulating strips of Low Lambda PA 66 GF25,
dry impact resistant**

Characteristic	Reference standard	Unit	Samples prepared from extruded insulating strips	
			Dry ⁽¹⁾	Equilibrium moisture content ⁽²⁾
melting temperature	EN ISO 11357-3	°C	min. 250 ⁽³⁾	min. 250 ⁽³⁾
density	EN ISO 1183-1 or -3	g/cm ³	1.0 +/- 0.1	1.0 +/- 0.1
annealing residue (glass fibre content)	EN ISO 1172	%	25 +/- 2.5	25 +/- 2.5
shore hardness D	EN ISO 868	-	77 +/- 4 ⁽⁴⁾	67 +/- 4 ⁽⁴⁾
impact strength	EN ISO 179-1	kJ/m ²	min. 20 ⁽⁵⁾	min. 30 ⁽⁵⁾
tensile strength	EN ISO 527-2 and -4	N/mm ²	min. 50 ⁽⁶⁾	min. 35 ⁽⁶⁾
Young's modulus	EN ISO 527-2 and -4	N/mm ²	min. 2900 ⁽⁶⁾	min. 1300 ⁽⁶⁾
elongation at break	EN ISO 527-2 and -4	%	min. 3 ⁽⁶⁾	min. 8 ⁽⁶⁾

- ¹⁾ Sample water content less than 0.2 % by weight
- ²⁾ Fast conditioning acc. to EN ISO 1110 (23 °C / 50 %)
- ³⁾ Maximum temperature 300 °C
- ⁴⁾ Specimen thickness 2 mm, unstacked
- ⁵⁾ Specimen 2fU (50 mm x 10 mm x 2 mm)
- ⁶⁾ Specimen Type 1BA

In case of specific questions we gladly offer you our individual support.

Insulation solutions for windows, doors, and facades